

**AN/FGC-25, AN/FGC-25X, AN/FGC-26,  
AN/FGC-26X, AN/FGC-57, AN/FGC-161, and  
AN/FGC-162 Teletypewriter Sets**

Status: STD-B; NSN: 5815-00-503-3316 (AN/FGC-25)  
STD-B; NSN: 5815-00-392-5644 (AN/FGC-25X)  
STD-B; NSN: 5815-00-553-4710 (AN/FGC-26)  
STD-B; NSN: 5815-00-583-0065 (AN/FGC-26X)  
STD-A; NSN: 5815-00-167-1147 (AN/FGC-161)  
STD-A; NSN: 5815-00-030-7120 (AN/FGC-162)

Reference: TM 11-5815-244-12

General Information

These teletypewriter sets provide facilities for transmitting, monitoring, and receiving messages in communications centers. Messages can be transmitted from either the keyboard or the transmitter-distributor and received on either the page printer or the reperforator. All sets can supply line current. All sets are similar in appearance. Major functional differences are covered in the technical manual.

Technical Characteristics

Method of Transmitting-----Keyboard or transmitter-distributor

Method of Receiving-----Page copy or paper tape

Type of Signal:

AN/FGC-161 and AN/FGC-162-----60 microampere polar

All Others (Transmit)-----20 or 60 mA neutral

All Others (Receive)-----20 or 60 mA neutral or 30 mA polar

Operation Mode:

AN/FGC-161, -162-----Full duplex only

All others-----Full duplex or half duplex

Speed Option-----60, 66, 75, or 100 wpm

Power Requirement:

AN/FGC-25, -26, -57, -161, -162-----95 to 125 V AC or 190 to 250 V AC, 60 Hz

AN/FGC-25X, -26X-----95 to 125 V AC or 190 to 250 V AC, 50  
to 60 Hz

Weight-----87.9 kg (192 lb)

**AN/FGC-25, AN/FGC-25X, AN/FGC-26,  
AN/FGC-26X, AN/FGC-57, AN/FGC-161, and  
AN/FGC-162 Teletypewriter Sets**

