

35Z4-GT



35Z4-GT HALF-WAVE VACUUM RECTIFIER

GENERAL DATA

Electrical:


Heater, for Unipotential Cathode:

Voltage 35 ac or dc volts
Current 0.15 amp

Mechanical:

Mounting Position Any
Maximum Overall Length 3-5/16"
Maximum Seated Length 2-3/4"
Maximum Diameter 1-5/16"
Bulb T-9
Base Intermediate-Shell Octal 6-Pin
Basing Designation for BOTTOM VIEW G-5AA

Pin 1 - No Connection
Pin 2 - Heater
Pin 3 - No Connection



Pin 5 - Plate
Pin 7 - Heater
Pin 8 - Cathode

HALF-WAVE RECTIFIER

Maximum Ratings, Design-Center Values:

PEAK INVERSE PLATE VOLTAGE 700 max. volts
PEAK PLATE CURRENT 600 max. ma.
DC OUTPUT CURRENT 100 max. ma.
PEAK HEATER-CATHODE VOLTAGE:
Heater negative with respect to cathode 350 max. volts
Heater positive with respect to cathode 350 max. volts

Typical Operation with Capacitor-Input Filter:

AC Plate-Supply Voltage (RMS) 117 235 volts
Min. Total Effective Plate-Supply Imped.[▲] 15 100 ohms
DC Output Current 100 100 ma.

[▲] When a filter-input capacitor larger than 40 μ f is used, it may be necessary to use more plate-supply impedance than the minimum value shown to limit the peak plate current to the rated value.

Curves under Type 35Z5-GT also apply to the 35Z4-GT

AVERAGE PLATE CHARACTERISTIC

