



**19AU4-GTA**  
**19BG6-GA**  
**19CL8-A**  
**19EA8**  
**19EZ8**  
**19J6**  
**19T8**  
**ET-T934B**

Page 1  
3-60

## DESCRIPTION AND RATING

**19AU4-GTA Diode.** Identical to the 6AU4-GTA except for heater ratings and addition of a controlled heater-warm-up characteristic. Refer to the 6AU4-GTA Description and Rating sheet for complete data.

**19BG6-GA Beam Pentode.** Identical to the 6BG6-GA except for heater ratings. Refer to the 6BG6-GA Description and Rating for complete data.

**19CL8-A Triode-Tetrode.** Identical to the 6CL8-A except for the following ratings:

Heater Voltage, AC or DC . . . . .	18.9	Volts
Heater Current . . . . .	.015	Amperes
Allowable Heater Current . . . . .	0.14 to 0.16	Amperes

**19EA8 Triode-Pentode.** Identical to the 6EA8 except for the following ratings:

Heater Voltage, AC or DC . . . . .	18.9	Volts
Heater Current . . . . .	.015	Amperes
Allowable Heater Current . . . . .	0.14 to 0.16	Amperes

**19EZ8 Triple-Triode.** Identical to the 6EZ8 except for the following ratings:

Cathode—Coated Unipotential		
Heater Voltage, AC or DC . . . . .	18.9 ± 10%	Volts
Heater Current . . . . .	.015	Amperes

**19J6 Twin Triode.** Identical to the 6J6 except for heater ratings. Refer to the 6J6 Description and Rating sheet for complete data.

**19T8 Triple-Diode Triode.** Identical to the 6T8 except for heater ratings. Refer to the 6T8 Description and Rating sheet for complete data.

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or elements. In the absence of an express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.

