

# 3DZ4

## Medium-Mu Triode

### 7-PIN MINIATURE TYPE

*The 3DZ4 is the same as the 6DZ4 except for the following items:*

Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450. . . . .	3.2	volts
Warm-up time (Average) . . . . .	11	sec
Peak heater-cathode voltage:		
Heater negative with respect to cathode . . . . .	180 max.	volts
Heater positive with respect to cathode . . . . .	180 <sup>b</sup> max.	sec

# 3EA5

## Sharp-Cutoff Tetrode

### 7-PIN MINIATURE TYPE

*The 3EA5 is the same as the 6EA5 except for the following items:*

Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450. . . . .	2.9	volts
Warm-up time (Average) . . . . .	11	sec

# 3EH7

## Semiremote-Cutoff Pentode

### 9-PIN MINIATURE TYPE

*The 3EH7 is the same as the 6EH7 except for the following items:*

Heater Characteristics and Ratings:

Current. . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600. . . . .	3.4	volts

<sup>b</sup> The dc component must not exceed 100 volts.

